

Fiche Technique

IT12137

IPC FULL COLOR

4.0MP IP DARK LIGHT TUBE Camera

Form parameters

Video&Audio	Image Sensor	1/2.8" 4MP 2K CMOS color Sensor
	Resolution	4MP/5MP
	Effective Pixels Main stream	2560×1440. 2880×1616. 2304×1296. 1920×1080. 1280×720
	Sub stream	704×576. 800×448. 640×480. 640×360. 352×288
	Video Compression	H.265/H.264
	Audio Compression	G.711u
	TV System	PAL/NTSC
	Frame Rate	1-30 FPS
	Bit Rate	128Kbps~8Mbps
	Synchronization	Internal
	SNR	>80dB
	Min Illumination	0.001 lux a (F : 1.0.AGC active). 0 lux avec Smart Warm light on
	Built-in micro	Optional
Lens	Focus Mount	M12
	Lens	4mm(2.8,3.6,6mm optional)
	Viewing Angle	80°
	Focus Control	Manual
	Exposure Mode	Auto
Function	Gain Control	Auto
	White Balance	Auto
	Digital Noise Reduction	3D DNR
	Network Time	Support
	Scheduled Restart	Support
	ROI	Support
	Defog	N/A
	Privacy Mask	Support 4 rectangle areas
	Motion Detection	Support
	Human Detection	Support
	Video Adjust	Supports contrast, brightness, saturation, sharpness adjustment
	Scene	Photoresistor,Scene brightness
	Day & Night	AUTO,always DAY,Always NIGHT,Timing DAY
	Lampe setting	White Lampe,Dual Lampe,Infrared Lampe
	Electronic screen	Support Exposure time setting, solve view electronic screen problem
	Night vision	Day & Night COLORFULL
	Wide Dynamic Range	Digital WDR



DARK LIGHT CAMERA:

4.0M@30fps,H.265/H.264 video compression (DWDR camera) ;

Using new generation 4 million star optical sensor with F1.0 large aperture lens; Support image style switching, support transparent, bright, soft three image style modes; Support motion detection, mobile detection alarm automatically send email reminder; Support software upgrade, available website upgrade / local upgrade;

Dual stream, user can select the stream and adjust the resolution, frame rate and videoquality; Support audio input to achieve perfect monitoring of video recording; one-button remote, network plug and play; Support the ONVIF protocol to ensure interconnection and intercommunication of network video surveillance products;

Fiche Technique

360[®] VISION

Function	Image setting	Mirror, Rotate
	IP Self-Adaption	Support
	Alarm	E-mail, Client
	Remote Operation	System, Stream, User, Network Management
	Audio input	Optional
	Alarme input	Optional
	Alarme output	Optional
	Ethernet	1 RJ45 10M/100M Adaptive Ethernet Interface
Network	Tri-Stream	Support
	Protocol	Support HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, PPPOE, P2P
	System Compatibility	ONVIF
	Transmission	Internal Protocol
	Management Software	Support IOS, Android
	Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+browsers
	Remote Connection	10CH
	User Permission	Up to 10 users
General	White Light Range	Warm white LEDs (3000K), Open area
	LED Portée distance	De 30 Jusqu'à 50m 8*Warm light leds
	Power Supply	DC 12V
	POE Power	Optional (IEEE 802.3af)
	Ingress Protection	IP66
	Working Temperature	-20℃ ~ +60℃
	Working Humidity	10% ~ 90%
	Consumption	Day: <3W Night: <6W
	Material	Metal
	Size(W×H×D) (mm)	232x73x80mm
	Weight (g)	420g



Resolution 2560x1440@30fps

Open area 8*Warm light leds

Support on iOS/Android

4mm wide angle lens 80°

Built-in Microphone Optional

Built-in POE optional

Built-in Alarme input Optional

Built-in Alarme output Optional

La conception et les spécifications peuvent être modifiées sans préavis. En aucun cas, ce document ne pourra être reproduit, distribué ou modifié partiellement ou totalement sans l'autorisation formelle de INTERNATIONAL TRADING GROUP.